VACUUM PUMP SYSTEM SC 920 G



22 rue de l'Hermite 33520 BRUGES Tél. +33 (0) 5 56 16 20 16 - Fax. +33 (0) 5 56 57 68 0 contact@atlanticlabo-ics.fr www.atlanticlabo-ics.f



Technical features

- Remote-controlled for safe operation from outside closed fume hoods
- Automatic, accurate recognition and monitoring of the boiling point using the integrated ramp function
- High recovery rates even with low boiling point solvents
- Integrated gas ballast valve
- Speed-controlled
- Quiet operation
- Optimized suction capacity
- PPS pump head combined with PTFE-coated diaphragm are ideal for aggressive/corrosive gases and vapors

Technical data

Flow rate [m³/h] at atm. pressure	1.26	
Flow rate [l/min] at atm. pressure	21	
Ultimate vacuum [mbar abs.]	2.0 < 5.0 with gas ballast valve in use	
Nominal voltage [V]	100 – 240	
Frequency [Hz]	50 – 60	
Power P ₁ [W]	max. 135	
Operating current [A]	max. 1.7	
With overcurrent protection and main fuse		

MATERIALS

Pump head	PPS
Diaphragm	PTFE-coated
Valves	FFPM
Separators	plastic-coated glass

OTHER DATA

Total weight [kg]	15.2	
Hose connections: – pneumatic – for coolants – for inert gas	ID 10 ID 8 ID 6	
Dimensions W x H x D [mm]	366 x 423 x 294	
Gas ballast valve	Yes	
Size of the separators [ml]	500	
USB connection	Mini-USB	
Permissible media and ambient temperature [°C]	+5 +40	

REMOTE CONTROL UNIT

Quantity	1
Display	LCD
Wireless range	About 50 m without obstaclesAbout 10 m through walls
Power supply	Through integrated batteries or included power supply
Battery service life	Up to 12 hours
Charging time	About 7 hours
Operation	Touchscreen/Control knob

ACCESSORIES	ID
Coolant valve – G 1/2, ID 8	117121
Column fixture for remote control unit	120132
Wall fixture for remote control unit	120130
Chemical-resistant protective film for remote control's display	117407
Charging station	129478

Combination possibilities



